



Product pictures are with accessories.

PRODUCT INFORMATION:

Nominal heat output:	6 kW
Energy efficiency:	81 %
CO%:	0,07 %

PRODUCT NUMBERS:

Product	Product number	Weight kg	Height mm
DEKO UNO S 1	703350-1	361	1200
DEKO UNO S 2	703350-2	341	1200
DEKO UNO S 3	703350-3	341	1200

ACCESSORIES:

Product	Product number	Weight kg	Height mm
Bottom plinth US	707941	37	102
Floor protector DS/US white	920333		
Floor protector DS/US black	920331		
Replacement air damper	920352		

PRODUCT INFORMATION

	FIREWOOD		FLUE CALCULATION VALUES ⁽¹⁾				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Length [cm]	Max amount of wood [kg/h]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Deko Uno S	25	1,65	255	-12	6,6	150	499

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]	INCOMING AIR
	round Ø	Incoming air pipe location L [mm]
Deko Uno S	150	217

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	CE-approval according to EN 13240		
	Behind	On the sides	Front
Deko Uno S	350	300	1100

¹⁾ The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards.

Take a notice of the countryspecific approvals in section 3

NOTES!

The flue heat category required by the fireplace is T600.

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue.

Country- and region-specific regulations must be adhered to when installing the fireplace

